

# FICHES DE DONNÉES DE SÉCURITÉ



Revision Date 12-Jul-2017  
Version 1

## 1. SECTION 01: Identification du produit et de la société chimique

### 1.1 Product identifier

Nom du produit EPOXY THINNER  
Product code RX590361-5

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Utilisation recommandée Paint Thinner for Antifouling Paints  
Utilisations contre-indiquées Read label instructions and SDS

### 1.3 Details of the supplier of the safety data sheet

Fabriqué pour  
Rexall Laboratories and Chemicals  
445 Eastchester Ave E, UNIT 4  
St. Catharines, ON L2M 6S2

1.4 numéro d'urgence 24 heures : CANUTEC's 24-hour number (1-888-CAN-UTEC(226-8832) or 613-996-6666)

## 2. SECTION 02: Identification des dangers

### 2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910.1200

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2

## 2.2 Label elements

### Signal Word

Danger

### Hazard Statements

Causes skin irritation  
Causes serious eye damage  
Suspected of causing cancer  
Suspected of damaging fertility or the unborn child  
May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways  
Highly flammable liquid and vapor



### Precautionary Statements - Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Wear protective gloves/protective clothing/eye protection/face protection  
Wash face, hands and any exposed skin thoroughly after handling  
Do not breathe dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Keep container tightly closed  
Ground/Bond container and receiving equipment  
Use explosion-proof electrical/ventilating/lighting/equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

### Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a POISON CENTER or doctor  
If skin irritation occurs: Get medical advice/attention  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
Wash contaminated clothing before reuse  
IF INHALED: Remove person to fresh air and keep comfortable for breathing  
IF SWALLOWED: Immediately call a POISON CENTER or doctor  
Do NOT induce vomiting  
In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish

### Precautionary Statements - Storage

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

## 2.3. Other Hazards Hazards not otherwise classified (HNOC)

Not Applicable

## 2.4 Other information

Not Applicable

**Unknown Acute Toxicity** < 1% of the mixture consists of ingredient(s) of unknown toxicity

### 3. Composition/Information on Ingredients

**Substance**

Not applicable

**Mixture**

Chemical Name	CAS-No	Weight %
Toluene	108-88-3	30 - 40
Xylene	1330-20-7	20 - 30
Methyl isobutyl ketone	108-10-1	10 - 20
Isopropyl alcohol	67-63-0	10 - 20
n-Propanol	71-23-8	5 - 10
Ethylbenzene	100-41-4	5 - 10
2,6-Dimethylheptan-4-one	108-83-8	1 - 5
CUMENE	98-82-8	< 1

The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First aid measures

#### 4.1 Description of first-aid measures

- General advice** For further assistance, contact your local Poison Control Center.
- Eye contact** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Call a poison control center or doctor for treatment advice.
- Skin contact** Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Call a poison control center or doctor for treatment advice.
- Inhalation** Move victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a poison control center or doctor for treatment advice.
- Ingestion** Rinse mouth. Do NOT induce vomiting. If a person vomits when lying on his back, place him in the recovery position. Call a physician or poison control center immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

**Symptoms** See Section 2.2, Label Elements and/or Section 11, Toxicological effects.

#### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician** There is no specific antidote for effects from overexposure to this material. Treat symptomatically.

### 5. Fire-Fighting Measures

#### 5.1 Extinguishing media

**Suitable extinguishing media**

Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray or fog. Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

**Unsuitable Extinguishing Media** Water may be unsuitable for extinguishing fires.

#### 5.2 Special hazards arising from the substance or mixture

**Special Hazard**

Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) Vapors may travel to areas away from work site before igniting/flashing back to vapor source Thermal decomposition can lead to release of irritating gases and vapors

**Hazardous Combustion Products** Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

**Explosion Data**

**Sensitivity to Mechanical Impact** Not sensitive.

**Sensitivity to Static Discharge** Yes.

**5.3 Advice for firefighters**

Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers with flooding quantities of water until well after fire is out. Thoroughly decontaminate all protective equipment after use. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

**6. Accidental Release Measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. Refer to protective measures listed in sections 7 and 8. Avoid exceeding of the given occupational exposure limits (see section 8). Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill.

**6.2 Environmental precautions**

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

**6.3 Methods and materials for containment and cleaning up**

**Methods for Containment** Dike far ahead of liquid spill for later disposal. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Ground and bond containers when transferring material. Take precautionary measures against static discharges. Use non-sparking tools and equipment.

**7. Handling and storage**

**7.1 Precautions for safe handling**

**Advice on safe handling** Ensure adequate ventilation. Ground and bond containers when transferring material. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product. Use according to package label instructions. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. No smoking.

**Hygiene measures** Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage Conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in properly labeled containers. Keep away from food, drink and animal feedingstuffs. Store in accordance with local regulations.

**Materials to Avoid**

No materials to be especially mentioned.

**8. Exposure controls/personal protection**

**8.1 Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	British Columbia	Alberta	Quebec	Ontario TWAEV
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm	TWA: 20 ppm Adverse reproductive effect	TWA: 50 ppm TWA: 188 mg/m <sup>3</sup> Skin	TWA: 50 ppm TWA: 188 mg/m <sup>3</sup> Skin	TWA: 20 ppm
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>	TWA: 100 ppm STEL: 150 ppm
Methyl isobutyl ketone 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m <sup>3</sup>	TWA: 20 ppm STEL: 75 ppm	TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 307 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 307 mg/m <sup>3</sup>	TWA: 20 ppm STEL: 75 ppm
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup>	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm TWA: 492 mg/m <sup>3</sup> STEL: 400 ppm STEL: 984 mg/m <sup>3</sup>	TWA: 400 ppm TWA: 985 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1230 mg/m <sup>3</sup>	TWA: 200 ppm STEL: 400 ppm
n-Propanol 71-23-8	TWA: 100 ppm	TWA: 200 ppm TWA: 500 mg/m <sup>3</sup>	TWA: 100 ppm	TWA: 200 ppm TWA: 492 mg/m <sup>3</sup> STEL: 400 ppm STEL: 984 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 492 mg/m <sup>3</sup> STEL: 250 ppm STEL: 614 mg/m <sup>3</sup> Skin	TWA: 100 ppm
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	TWA: 20 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	TWA: 20 ppm
2,6-Dimethylheptan-4-one 108-83-8	TWA: 25 ppm	TWA: 50 ppm TWA: 290 mg/m <sup>3</sup>	TWA: 25 ppm	TWA: 25 ppm TWA: 145 mg/m <sup>3</sup>	TWA: 25 ppm TWA: 145 mg/m <sup>3</sup>	TWA: 25 ppm
CUMENE 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> S*	TWA: 25 ppm STEL: 75 ppm	TWA: 50 ppm TWA: 246 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 246 mg/m <sup>3</sup>	TWA: 50 ppm

**8.2 Appropriate engineering controls**

**Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use adequate ventilation to maintain airborne concentrations at levels below permissible or recommended occupational exposure limits.

**8.3 Individual protection measures, such as personal protective equipment**

**Eye/Face Protection**

Safety glasses with side-shields. If splashes are likely to occur, wear: Tightly fitting safety goggles.

**Skin and body protection**

Solvent-resistant gloves. Nitrile rubber. Neoprene gloves. Impervious butyl rubber gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Wear suitable protective clothing. Remove and wash contaminated clothing before re-use.

**Respiratory protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

See section 7 for more information

**9. Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

Physical state	Liquid
Appearance	No information available
Color	Clear
Odor	Ketones
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>
pH		No information available
Melting/freezing point		No information available
Boiling point/boiling range	82 °C / 180 °F	-For pure isopropyl alcohol
Flash Point	7 °C / 45 °F	
Evaporation rate		No information available
Flammability (solid, gas)		No information available
Flammability Limits in Air		
upper flammability limit		No information available
lower flammability limit		No information available
Vapor pressure		No information available
Vapor density		No information available
Specific Gravity		No information available
Water solubility		No information available
Solubility in other solvents		No information available
Partition coefficient		No information available
Autoignition temperature		No information available
Decomposition temperature		No information available
Viscosity, kinematic	< 20 mm <sup>2</sup> /s	
Viscosity, dynamic		No information available
Explosive properties		No information available
Oxidizing Properties		No information available

**9.2 Other information**

Volatile organic compounds (VOC) content	841 g/L
Density	7.02 lb/gal

**10. Stability and Reactivity**

**10.1 Reactivity**

No dangerous reaction known under conditions of normal use

**10.2 Chemical stability**

Stable under recommended storage conditions

**10.3 Possibility of hazardous reactions**

None under normal processing.

**10.4 Conditions to Avoid**

Keep away from heat, sparks and flames.

**10.5 Incompatible Materials**

No materials to be especially mentioned.

## 10.6 Hazardous Decomposition Products

None under normal use conditions. Thermal decomposition can lead to release of irritating gases and vapors.

## 11. Toxicological information

### 11.1 Acute toxicity

#### Numerical measures of toxicity: Product Information

The following values are calculated based on chapter 3.1 of the GHS document

**Unknown Acute Toxicity** < 1% of the mixture consists of ingredient(s) of unknown toxicity

<b>Oral LD50</b>	2,819.00 mg/kg
<b>Dermal LD50</b>	5,139.00 mg/kg
<b>LC50 (Dust/Mist)</b>	7.50 mg/l
<b>LC50 (Vapor)</b>	29.00 mg/l

#### Numerical measures of toxicity: Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene 108-88-3	2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 28.1 mg/L ( Rat ) 4 h
Xylene 1330-20-7	3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h
Methyl isobutyl ketone 108-10-1	2080 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	> 2000 ppm ( Rat ) 4 h
Isopropyl alcohol 67-63-0	5840 mg/kg ( Rat )	= 13,900 mg/kg ( Rabbit )	= 72600 mg/m <sup>3</sup> ( Rat ) 4 h
n-Propanol 71-23-8	3830 mg/kg ( Rat )	> 10000 mg/kg ( Rabbit )	> 13548 ppm ( Rat ) 4 h
Ethylbenzene 100-41-4	3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h
2,6-Dimethylheptan-4-one 108-83-8	-	-	> 2300 ppm ( Rat ) 4 h
CUMENE 98-82-8	1400 mg/kg ( Rat )	= 12300 µL/kg ( Rabbit )	8700 ppm (Rat) 4-h

### 11.2 Information on toxicological effects

#### Skin corrosion/irritation

##### Product Information

- No information available

##### Component Information

- No information available

#### Serious eye damage/eye irritation

##### Product Information

- No information available

##### Component Information

- No information available

#### Respiratory or skin sensitization

##### Product Information

- No information available

##### Component Information

- No information available

#### Germ cell mutagenicity

##### Product Information

- No information available

- EPOXY THINNER

Component Information

- No information available

**Carcinogenicity**

Product Information

- The table below indicates whether each agency has listed any ingredient as a carcinogen

Component Information

- Contains a known or suspected carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Methyl isobutyl ketone 108-10-1	-	Group 2B	-	
Isopropyl alcohol 67-63-0	-	Group 3	-	
Ethylbenzene 100-41-4	-	Group 2B	-	
CUMENE 98-82-8	-	Group 2B	Reasonably Anticipated	

**Reproductive toxicity**

Product Information

- No information available

Component Information

- No information available

**STOT - single exposure**

No information available

**STOT - repeated exposure**

No information available

**Other adverse effects**

Product Information

- No information available

Component Information

- No information available

**Aspiration hazard**

Product Information

- No information available

Component Information

- No information available

**12. Ecological information**

**12.1 Toxicity**

**Ecotoxicity**

No information available

< 1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

**Ecotoxicity effects**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Toluene 108-88-3	EC50: 96 h Pseudokirchneriella subcapitata 433 mg/L EC50: 72 h Pseudokirchneriella subcapitata 12.5 mg/L static	LC50: 96 h Pimephales promelas 15.22 - 19.05 mg/L flow-through LC50: 96 h Pimephales promelas 12.6 mg/L static LC50: 96 h Oncorhynchus mykiss 5.89 - 7.81 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 14.1 - 17.16 mg/L static LC50: 96 h Oncorhynchus mykiss 5.8 mg/L	EC50: 48 h Daphnia magna 5.46 - 9.83 mg/L Static EC50: 48 h Daphnia magna 11.5 mg/L



- EPOXY THINNER

		semi-static LC50: 96 h <i>Lepomis macrochirus</i> 11.0 - 15.0 mg/L static LC50: 96 h <i>Oryzias latipes</i> 54 mg/L static LC50: 96 h <i>Poecilia reticulata</i> 28.2 mg/L semi-static LC50: 96 h <i>Poecilia reticulata</i> 50.87 - 70.34 mg/L static	
Xylene 1330-20-7	-	LC50: 96 h <i>Pimephales promelas</i> 23.53 - 29.97 mg/L static LC50: 96 h <i>Cyprinus carpio</i> 780 mg/L semi-static LC50: 96 h <i>Cyprinus carpio</i> 780 mg/L LC50: 96 h <i>Poecilia reticulata</i> 30.26 - 40.75 mg/L static LC50: 96 h <i>Pimephales promelas</i> 13.4 mg/L flow-through LC50: 96 h <i>Oncorhynchus mykiss</i> 2.661 - 4.093 mg/L static LC50: 96 h <i>Oncorhynchus mykiss</i> 13.5 - 17.3 mg/L LC50: 96 h <i>Lepomis macrochirus</i> 13.1 - 16.5 mg/L flow-through LC50: 96 h <i>Lepomis macrochirus</i> 19 mg/L LC50: 96 h <i>Lepomis macrochirus</i> 7.711 - 9.591 mg/L static	EC50: 48 h water flea 3.82 mg/L LC50: 48 h <i>Gammarus lacustris</i> 0.6 mg/L
Methyl isobutyl ketone 108-10-1	EC50: 96 h <i>Pseudokirchneriella subcapitata</i> 400 mg/L	LC50: 96 h <i>Pimephales promelas</i> 496 - 514 mg/L flow-through	EC50: 48 h <i>Daphnia magna</i> 170 mg/L
Isopropyl alcohol 67-63-0	EC50: 96 h <i>Desmodesmus subspicatus</i> 1000 mg/L EC50: 72 h <i>Desmodesmus subspicatus</i> 1000 mg/L	LC50: 96 h <i>Pimephales promelas</i> 9640 mg/L flow-through LC50: 96 h <i>Pimephales promelas</i> 11130 mg/L static LC50: 96 h <i>Lepomis macrochirus</i> 1400000 µg/L	EC50: 48 h <i>Daphnia magna</i> 13299 mg/L
n-Propanol 71-23-8	-	LC50: 96 h <i>Pimephales promelas</i> 4480 mg/L flow-through	EC50: 48 h <i>Daphnia magna</i> 3642 mg/L EC50: 48 h <i>Daphnia magna</i> 3339 - 3977 mg/L Static
Ethylbenzene 100-41-4	EC50: 72 h <i>Pseudokirchneriella subcapitata</i> 4.6 mg/L EC50: 96 h <i>Pseudokirchneriella subcapitata</i> 438 mg/L EC50: 72 h <i>Pseudokirchneriella subcapitata</i> 2.6 - 11.3 mg/L static EC50: 96 h <i>Pseudokirchneriella subcapitata</i> 1.7 - 7.6 mg/L static	LC50: 96 h <i>Oncorhynchus mykiss</i> 11.0 - 18.0 mg/L static LC50: 96 h <i>Oncorhynchus mykiss</i> 4.2 mg/L semi-static LC50: 96 h <i>Pimephales promelas</i> 7.55 - 11 mg/L flow-through LC50: 96 h <i>Lepomis macrochirus</i> 32 mg/L static LC50: 96 h <i>Pimephales promelas</i> 9.1 - 15.6 mg/L static LC50: 96 h <i>Poecilia reticulata</i> 9.6 mg/L static	EC50: 48 h <i>Daphnia magna</i> 1.8 - 2.4 mg/L
2,6-Dimethylheptan-4-one 108-83-8	EC50: 96 h <i>Pseudokirchneriella subcapitata</i> 100 mg/L	LC50: 96 h <i>Oncorhynchus mykiss</i> 140 mg/L semi-static	-
CUMENE 98-82-8	EC50: 72 h <i>Pseudokirchneriella subcapitata</i> 2.6 mg/L	LC50: 96 h <i>Pimephales promelas</i> 6.04 - 6.61 mg/L flow-through LC50: 96 h <i>Oncorhynchus mykiss</i> 4.8 mg/L flow-through LC50: 96 h <i>Oncorhynchus mykiss</i> 2.7 mg/L semi-static LC50: 96 h <i>Poecilia reticulata</i> 5.1 mg/L semi-static	EC50: 48 h <i>Daphnia magna</i> 0.6 mg/L EC50: 48 h <i>Daphnia magna</i> 7.9 - 14.1 mg/L Static

**12.2 Persistence and degradability**

No information available.

**12.3 Bioaccumulative potential**

Discharge into the environment must be avoided

Chemical Name	log Pow
Toluene 108-88-3	2.65
Xylene 1330-20-7	3.15
Methyl isobutyl ketone 108-10-1	1.19
Isopropyl alcohol	0.05

- EPOXY THINNER

67-63-0	
n-Propanol 71-23-8	0.34
Ethylbenzene 100-41-4	3.118
CUMENE 98-82-8	3.55

**12.4 Mobility in soil**

No information available.

**12.5 Other adverse effects**

No information available

**13. Disposal Considerations**

**13.1 Waste treatment methods**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**14. Transport Information**

**DOT**

DOT - Special Provision 149: UN1263, Paint or Paint related material, PGII: When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in CFR 49. 173.150(b)(2) of this subchapter for inner packagings may be increased to 5 L (1.3 gallons).

**Proper shipping name**

UN1263, Paint related material, 3, PG II

**MEX**

no data available

**IMDG**

**Proper shipping name**

UN1263, Paint related material, 3, PG II

**IATA**

**Proper shipping name**

UN1263, Paint related material, 3, PG II

**15. Regulatory information**

**15.1 International Inventories**

<b>TSCA</b>	Complies
<b>DSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies
<b>NZIoC</b>	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**15.2 U.S. Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %
Toluene 108-88-3	1.0
Xylene 1330-20-7	1.0
Methyl isobutyl ketone 108-10-1	1.0
Isopropyl alcohol 67-63-0	1.0
Ethylbenzene 100-41-4	0.1

**15.3 Pesticide Information**

Not applicable

**15.4 U.S. State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
Toluene - 108-88-3	Developmental Female Reproductive
Methyl isobutyl ketone - 108-10-1	Carcinogen Developmental
Ethylbenzene - 100-41-4	Carcinogen
CUMENE - 98-82-8	Carcinogen
Benzene - 71-43-2	Carcinogen Developmental Male Reproductive
Naphthalene - 91-20-3	Carcinogen

**16. Other information**

<b>NFPA</b>	<b>Health Hazard 3</b>	<b>Flammability 3</b>	<b>Instability 0</b>	<b>Physical and chemical hazards -</b>
<b>HMIS</b>	<b>Health Hazard 3*</b>	<b>Flammability 3</b>	<b>Physical Hazard 0</b>	<b>Personal protection X</b>

**Legend:**

- ACGIH (American Conference of Governmental Industrial Hygienists)
- Ceiling (C)
- DOT (Department of Transportation)
- EPA (Environmental Protection Agency)
- IARC (International Agency for Research on Cancer)
- International Air Transport Association (IATA)
- International Maritime Dangerous Goods (IMDG)
- NIOSH (National Institute for Occupational Safety and Health)
- NTP (National Toxicology Program)
- OSHA (Occupational Safety and Health Administration of the US Department of Labor)
- PEL (Permissible Exposure Limit)
- Reportable Quantity (RQ)
- Skin designation (S\*)
- STEL (Short Term Exposure Limit)
- TLV® (Threshold Limit Value)
- TWA (time-weighted average)

**Revision Date** 12-Jul-2016

**Revision Note**  
No information available

**Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**