

1. IDENTIFICATION

1.1 Product identifiers

Product Name : Isopropyl Alcohol 99%

Brand : Rexall Solutions

Poduct Code: RX590263,

Product Use : Disinfectant solvent; For laoboratory research purposes.

1.2 Details of the supplier of the safety data sheet

Manufacturer Rexall Solutions 27 Keefer Rd, St. Catharines, ON L2M 6K4

1.3 Emergency telephone number

Emergency Phone # : CANUTEC's 24-hour number (1-888-CAN-UTEC (226-8832) or 613-996-6666)

2. HAZARDS IDENTIFICATION

Emergency Overview

Other hazards which do not result in classification May form explosive peroxides.

WHMIS Classification

B2Flammable liquidD2BToxic Material Causing Other Toxic Effects

Flammable liquid Moderate eye irritant

GHS Classification

Flammable liquids (Category 2) Skin irritation (Category 3) Eye irritation (Category 2A) Specific target organ toxicity - single exposure (Category 3)

GHS Label elements, including precautionary statements

Pictogram



Signal word	Danger
Hazard statement(s) H225 H316 H319 H336	Highly flammable liquid and vapour. Causes mild skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statement(s) P210 P261 P305 + P351 + P338	Keep away from heat/sparks/open flames/hot surfaces No smoking. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Health hazard: Chronic Health Hazard:	2 *
Flammability:	3
Physical hazards:	0
Reactivity:	1
FPA Rating	
Health hazard:	2
Fire:	3
Reactivity Hazard:	1

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms	: Isopropanol		
Formula Molecular Weight	: C ₃ H ₈ O : 60.10 g/mol		
CAS-No.	EC-No.	Index-No.	Concentration
2-Propanol			
67-63-0	200-661-7	603-117-00-0	<=100%

4. FIRST AID MEASURES

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

Ν

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIREFIGHTING MEASURES

Conditions of flammability

Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special protective equipment for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous combustion products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Explosion data - sensitivity to mechanical impact no data available

Explosion data - sensitivity to static discharge no data available

Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Handle and store under inert gas. Hygroscopic.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
2-Propanol	67-63-0	TWAEV	400 ppm 983 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	200 ppm	Canada. British Columbia OEL
		STEL	400 ppm	Canada. British Columbia OEL
		STEL	400 ppm 984 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	200 ppm 492 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		STEL	500 ppm 1,230 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	400 ppm 983 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		STEV	500 ppm 1,230 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	400 ppm	USA. ACGIH Threshold Limit Values (TLV)

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 480 min Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.2 mm Break through time: 60 min Material tested:Dermatril® P (KCL 743 / Aldrich Z677388, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

impervious clothing, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Specific engineering controls

Use mechanical exhaust or laboratory fumehood to avoid exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form		liquid
Colou	ur	colourless
Safety d	lata	
pН		no data available
Meltir point/	ng /freezing point	-89.5 °C (-129.1 °F)
Boilin	ng point	81.0 - 83.0 °C (177.8 - 181.4 °F)
Flash	n point	12.0 °C (53.6 °F) - closed cup
Ignitio	on temperature	425 °C (797 °F)
	-ignition erature	425.0 °C (797.0 °F)
Lowe	er explosion limit	2 %(V)

Upper explosion limit	12.7 %(V)
Vapour pressure	43.2 hPa (32.4 mmHg) at 20.0 °C (68.0 °F) 58.7 hPa (44.0 mmHg) at 25.0 °C (77.0 °F)
Density	0.78 g/cm3
Water solubility	completely soluble
Partition coefficient: n-octanol/water	log Pow: 0.05
Relative vapour density	no data available
Odour	alcohol-like
Odour Threshold	no data available
Evapouration rate	3.0

10. STABILITY AND REACTIVITY

Chemical stability

Stable under recommended storage conditions. Test for peroxide formation before distillation or evaporation. Test for peroxide formation or discard after 1 year.

Possibility of hazardous reactions

Vapours may form explosive mixture with air.

Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Materials to avoid

Oxidizing agents, Acid anhydrides, Aluminium, Halogenated compounds, Acids

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - no data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Oral LD50

LD50 Oral - rat - 5,045 mg/kg Remarks: Behavioral:Altered sleep time (including change in righting reflex). Behavioral:Somnolence (general depressed activity).

Inhalation LC50 LC50 Inhalation - rat - 8 h - 16000 ppm

Dermal LD50 LD50 Dermal - rabbit - 12,800 mg/kg

Other information on acute toxicity no data available

Skin corrosion/irritation Skin - rabbit - Mild skin irritation

Serious eye damage/eye irritation Eyes - rabbit - Eye irritation - 24 h

Respiratory or skin sensitisation no data available

Germ cell mutagenicity

no data available

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (2-Propanol)

Reproductive toxicity

no data available

Teratogenicity

no data available

Specific target organ toxicity - single exposure (Globally Harmonized System) Inhalation, Oral - May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure (Globally Harmonized System) no data available

Aspiration hazard

no data available

Signs and Symptoms of Exposure

Central nervous system depression, prolonged or repeated exposure can cause:, Nausea, Headache, Vomiting, narcosis, Drowsiness, Overexposure may cause mild, reversible liver effects., Aspiration may lead to:, Lung oedema, Pneumonia

Synergistic effects no data available

Additional Information

RTECS: NT8050000

12. ECOLOGICAL INFORMATION

Toxicity

Toxicity to fish	LC50 - Pimephales promelas (fathead minnow) - 9,640.00 mg/l - 96 h
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 5,102.00 mg/l - 24 h
	Immobilization EC50 - Daphnia magna (Water flea) - 6,851 mg/l - 24 h
Toxicity to algae	EC50 - Desmodesmus subspicatus (green algae) - > 2,000.00 mg/l - 72 h
	EC50 - Algae - > 1,000.00 mg/l - 24 h

Persistence and degradability

no data available

Bioaccumulative potential

No bioaccumulation is to be expected (log Pow <= 4).

Mobility in soil no data available

PBT and vPvB assessment

no data available

Other adverse effects

no data available

13. DISPOSAL CONSIDERATIONS

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)UN number: 1219Class: 3Packing group: IIProper shipping name: IsopropanolPacking group: IIReportable Quantity (RQ):Marine pollutant: NoMarine pollutant: NoPoison Inhalation Hazard: NoIMDGPacking group: IIUN number: 1219Class: 3Proper shipping name: ISOPROPANOLPacking group: II

ΙΑΤΑ

UN number: 1219	Class: 3	Packing group: II
Proper shipping name: Isopropanol		

15. REGULATORY INFORMATION

Marine pollutant: No

WHMIS Classification

B2 Flammable liquid D2B Toxic Material Causing Other Toxic Effects Flammable liquid Moderate eye irritant

EMS-No: F-E, S-D

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

16. OTHER INFORMATION

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Rexall Labs and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.