

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**Product identifier****Product Name** Lacquer Thinner, 4311**Product Code:** RX590245**Other means of identification** None**Synonyms****Recommended use of the chemical and restrictions on use****Recommended Use** Cleaning Tools, Spray Guns, Equipments**Uses advised against** No information available**Details of the supplier of the safety data sheet****Manufacture Name** Rexall Solutions**Manufacture Address** 27 Keefer Rd, St. Catharines, ON L2M 6K4
(905) 641-4555**Supplier Email** CANUTEC's 24-hour number (1-888-CAN-UTEC (226-8832) or 613-996-6666)**Emergency telephone number****2. HAZARDS IDENTIFICATION****Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)


Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 2

Lacquer Thinner

Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2

GHS Label elements, including precautionary statements

Emergency Overview

Signal word	Danger	
Hazard Statements Harmful if swallowed Harmful in contact with skin Harmful if inhaled Causes skin irritation Causes serious eye irritation May cause genetic defects Suspected of causing cancer Suspected of damaging fertility or the unborn child Causes damage to organs May cause damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways Highly flammable liquid and vapor		
		
Appearance Clear	Physical State Liquid	Odor Mild

Precautionary Statements - Prevention

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Do not breathe dust/fume/gas/mist/vapors/spray
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ ventilating/ lighting/ equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge

Precautionary Statements - Response

- Specific treatment (see supplemental first aid instructions on this label)
- IF exposed: Call a POISON CENTER or doctor/physician

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
If skin irritation occurs: Get medical advice/attention
Call a POISON CENTER or doctor/physician if you feel unwell
Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Ingestion

Rinse mouth
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Harmful to aquatic life with long lasting effects
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION
INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Ethylacetate	141-78-6	15 - 40	
Methyl alcohol	67-56-1	10 - 30	
Acetone	67-64-1	10 - 30	
Toluene	108-88-3	7 - 13	
Aliphatic Naphtha	64742-89-8	7 - 13	
Xylene	1330-20-7	5 - 10	
Methyl Ethyl Ketone	78-93-3	3 - 7	
Ethylbenzene	100-41-4	1 - 5	

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

<u>General Advice</u>	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen.
Ingestion	Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Call a physician or poison control center immediately.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects Burning sensation. Coughing and/ or wheezing. Difficulty in breathing. Dizziness.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical. Carbon dioxide (CO₂). Alcohol resistant foam.

Unsuitable Extinguishing Media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Vapors can form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

Uniform Fire Code

Flammable Liquid: I-B
Irritant: Liquid

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Full encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Stop leak if you can do it without risk.

Other Information

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental Precautions

Environmental Precautions

Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for Containment

A vapor suppressing foam may be used to reduce vapors. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up

Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid breathing vapors or mists. Use personal protection equipment. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Protect from moisture. Store away from other materials. Store locked up. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products

Strong acids. Strong oxidizing agents. Strong bases. Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethylacetate 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m ³
Methyl alcohol 67-56-1	STEL = 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 325 mg/m ³ STEL: 250 ppm
Acetone	STEL = 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 1800 mg/m ³ (vacated) TWA: 750 ppm (vacated) STEL: 1000 ppm (vacated) STEL: 2400 mg/m ³	IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m ³
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³

Lacquer Thinner

Methyl Ethyl Ketone	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 590 mg/m ³ (vacated) STEL: 300 ppm (vacated) STEL: 885 mg/m ³	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³
Xylene 1330-20-7	STEL = 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	
Ethylbenzene 100-41-4	STEL = 125 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm 10% LEL TWA: 100 ppm TWA: 435 mg/m ³ STEL: 545 mg/m ³ STEL: 125 ppm

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection If splashes are likely to occur: Tight sealing safety goggles.

Skin and Body Protection Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Chemical resistant apron. Antistatic boots.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State	Liquid	Odor	Mild
Appearance	Clear	Odor Threshold	No information available
Color	No information available		
Property	Values	Remarks/ Method	
pH	N/A	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	56 °C / 133 °F	None known	



Flash Point	-18 C / 0 F	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	Moderate	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing Properties	No data available	

Other Information

Softening Point	No data available
VOC Content (%)	90%
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Excessive heat. Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases. Chlorinated compounds.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Product does not present an acute toxicity hazard based on known or supplied information.

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Harmful by inhalation. (based on components). Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal.
Eye Contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation. May cause irritation.
Skin Contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation. May be absorbed through the skin in harmful amounts. Harmful in contact with skin. (based on components). Repeated exposure may cause skin dryness or cracking.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed. (based on components). Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylacetate 141-78-6	= 5620 mg/kg (Rat)	> 20 mL/kg (Rabbit)	-
Methyl alcohol 67-56-1	= 5628 mg/kg (Rat)	-	= 83.2 mg/L (Rat) 4 h
Acetone 67-64-1	-	-	= 50100 mg/m ³ (Rat) 8 h
Toluene 108-88-3	= 636 mg/kg (Rat)	= 8390 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h > 26700 ppm (Rat) 1 h
Aliphatic Naphtha 64742-89-8	-	-	= 23500 mg/m ³ (Rat) 8 h
Xylene 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 47635 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Methyl Ethyl Ketone 78-93-3	-	= 3000 mg/kg (Rabbit)	-
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15354 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. Coughing and/ or wheezing. Difficulty in breathing. Asthma-like and/ or skin allergy-like symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects There is no data available for this product. Contains a known or suspected mutagen.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Toluene 108-88-3		Group 3		
Xylene 1330-20-7		Group 3		

Lacquer Thinner

Ethylbenzene 100-41-4	A3	Group 2B		X
--------------------------	----	----------	--	---

ACGIH (American Conference of Governmental Industrial Hygienists)
A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
Group 2B - Possibly Carcinogenic to Humans
Group 3 - Not Classifiable as to Carcinogenicity in Humans
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Reproductive Toxicity	Product is or contains a chemical which is a known or suspected reproductive hazard. Contains a known or suspected reproductive toxin.
STOT - single exposure	Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). If this product is a mixture, the classification is not based on toxicology studies for this product, but is based solely on toxicology studies for ingredients found within this product. Detailed substance and/or ingredient information may be provided in other sections of this SDS. Target organs effects listed in this document may result from a single overexposure to this product. Causes damage to organs if swallowed. Causes damage to organs in contact with skin. Causes damage to organs if inhaled.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).
Chronic Toxicity	No known effect based on information supplied. Contains a known or suspected mutagen. Possible risk of irreversible effects. Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. Aspiration may cause pulmonary edema and pneumonitis. Effects from this product caused by acute exposure may cause permanent damage to target organs and/or may cause chronic conditions. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse liver effects. Contains toluene. Exposure to toluene in animals via inhalation and intentional overexposure to toluene in humans has caused adverse fetal development effects.
Target Organ Effects	Respiratory system. Eyes. Skin. May affect the genetic material in germ cells (sperm and eggs). Gastrointestinal tract (GI). Reproductive System. Central Nervous System (CNS). Kidney. Liver. Blood. Systemic Toxicity.
Aspiration Hazard	No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

427.00 mg/kg

ATEmix (dermal)

1,275.00 mg/kg (ATE)

ATEmix (inhalation-gas)

3,193.00 ppm (4 hr)

ATEmix (inhalation-dust/mist)

2.00 mg/l

ATEmix (inhalation-vapor)

13.00 ATEmix

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Harmful to aquatic life with long lasting effects.

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Ethylacetate 141-78-6	0.6
Methyl alcohol 67-56-1	-0.77
Acetone 67-64-1	-0.24
Toluene 108-88-3	2.65
Methyl Ethyl Ketone 78-93-3	0.29
Xylene 1330-20-7	2.77 - 3.15
Ethylbenzene 100-41-4	3.118

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number D001 D035 U220 U002 U154 U159 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Ethylacetate 141-78-6		Included in waste stream: F039		U112
Methyl alcohol 67-56-1		Included in waste stream: F039		U154
Acetone 67-64-1				U002
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220
Methyl Ethyl Ketone 78-93-3	waste number U159	Included in waste streams: F005, F039	= 200.0 mg/L regulatory level	U159
Xylene 1330-20-7		Included in waste stream: F039		U239
Ethylbenzene 100-41-4		Included in waste stream: F039		

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

California Hazardous Waste Codes 214

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Ethylacetate 141-78-6	Toxic Ignitable
Methyl alcohol 67-56-1	Toxic Ignitable
Acetone 67-64-1	Ignitable



Lacquer Thinner

Toluene 108-88-3	Toxic Ignitable
Methyl ethyl Ketone 78-93-3	Toxic Ignitable
Xylene 1330-20-7	Toxic Ignitable
Ethylbenzene 100-41-4	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN-No. UN1263
Proper Shipping Name PAINT RELATED MATERIAL
Hazard Class 3
Packing Group II
Description UN1263, PAINT RELATED MATERIAL, 3, PGII

TDG

UN-No. UN1992
Proper Shipping Name FLAMMABLE LIQUID, TOXIC, N.O.S.
Hazard Class 3
Subsidiary class (6.1)
Packing Group II
Description UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHYL ACETATE, METHANOL), 3 (6.1), II

MEX

UN-No. UN1992
Proper Shipping Name FLAMMABLE LIQUID, TOXIC, N.O.S.
Hazard Class 3
Subsidiary class 6.1
Packing Group II
Description UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHYL ACETATE, METHANOL), 3 (6.1), II

ICAO

UN-No. UN1992
Proper Shipping Name FLAMMABLE LIQUID, TOXIC, N.O.S.
Hazard Class 3
Subsidiary class 6.1
Packing Group II
Description UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHYL ACETATE, METHANOL), 3 (6.1), II

IATA

UN-No. UN1992
Proper Shipping Name FLAMMABLE LIQUID, TOXIC, N.O.S.
Hazard Class 3
Subsidiary class 6.1
Packing Group II
Description UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHYL ACETATE, METHANOL), 3 (6.1), II

IMDG/IMO

UN-No. UN1992
Proper Shipping Name FLAMMABLE LIQUID, TOXIC, N.O.S.
Hazard Class 3
Subsidiary class 6.1



Packing Group II
EmS No. F-E, S-D
Description UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHYL ACETATE, METHANOL), 3 (6.1), II, FP -18C

RID

UN-No. UN1992
Proper Shipping Name FLAMMABLE LIQUID, TOXIC, N.O.S.
Hazard Class 3
Packing Group II
Classification code FT1
Description UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHYL ACETATE, METHANOL), 3 (6.1), II
ADR/RID-Labels 6.1

ADR

UN-No. UN1992
Proper Shipping Name FLAMMABLE LIQUID, TOXIC, N.O.S.
Hazard Class 3
Packing Group II
Classification code FT1
Description UN1992 FLAMMABLE LIQUID, TOXIC, N.O.S.(METHYL ALCOHOL), 3(6.1), II
ADR/RID-Labels 6.1

ADN

UN-No. UN1992
Proper Shipping Name FLAMMABLE LIQUID, TOXIC, N.O.S.
Hazard Class 3
Packing Group II
Classification code FT1
Special Provisions 274, 802
Description UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHYL ACETATE, METHANOL), 3 (6.1), II
Hazard Labels 3 + 6.1
Limited Quantity 1 L
Ventilation VE01, VE02

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Methyl alcohol - 67-56-1	67-56-1	10 - 30	1.0
Toluene - 108-88-3	108-88-3	7 - 13	1.0
Xylene - 1330-20-7	1330-20-7	5 - 10	1.0
Ethylbenzene - 100-41-4	100-41-4	1 - 5	0.1

SARA 311/312 Hazard Categories



Lacquer Thinner

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene 108-88-3	1000 lb	X	X	X
Xylene 1330-20-7	100 lb			X
Ethylbenzene 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ethylacetate 141-78-6			RQ 5000 lb final RQ RQ 2270 kg final RQ
Methyl alcohol 67-56-1	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ
Acetone 67-64-1	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ
Toluene 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Methyl Ethyl Ketone 78-93-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylene 1330-20-7	100 lb		RQ= 100 lb final RQ RQ= 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ= 1000 lb final RQ RQ= 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Methyl alcohol - 67-56-1	Developmental
Toluene - 108-88-3	Developmental
Ethylbenzene - 100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Ethylacetate 141-78-6	X	X	X	X	
Methyl alcohol 67-56-1	X	X	X	X	X
Acetone 67-64-1	X	X	X	X	
Toluene 108-88-3	X	X	X	X	X
Methyl Ethyl Ketone 78-93-3	X	X	X	X	X



Lacquer Thinner

Xylene 1330-20-7	X	X	X	X	X
Ethylbenzene 100-41-4	X	X	X	X	X

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Ethylacetate 141-78-6 (15 - 40)		Mexico: TWA 400 ppm Mexico: TWA 1400 mg/m ³
Methyl alcohol 67-56-1 (10 - 30)		Mexico: TWA= 200 ppm Mexico: TWA= 260 mg/m ³ Mexico: STEL= 250 ppm Mexico: STEL= 310 mg/m ³
Acetone 67-64-1 (10 - 30)		Mexico: TWA= 1000 ppm Mexico: TWA= 2400 mg/m ³ Mexico: STEL= 1260 ppm Mexico: STEL= 3000 mg/m ³
Toluene 108-88-3 (7 - 13)		Mexico: TWA 50 ppm Mexico: TWA 188 mg/m ³
Methyl Ethyl Ketone 78-93-3 (7 - 13)		Mexico: TWA= 590 mg/m ³ Mexico: TWA= 200 ppm Mexico: STEL= 885 mg/m ³ Mexico: STEL= 300 ppm
Xylene 1330-20-7 (5 - 10)		Mexico: TWA= 100 ppm Mexico: TWA= 435 mg/m ³ Mexico: STEL= 150 ppm Mexico: STEL= 655 mg/m ³
Ethylbenzene 100-41-4 (1 - 5)		Mexico: TWA= 435 mg/m ³ Mexico: TWA= 100 ppm Mexico: STEL= 125 ppm Mexico: STEL= 545 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

B2 - Flammable liquid

D2A - Very toxic materials



16. OTHER INFORMATION

NFPA	Health Hazards 3	Flammability 3	Instability 0	Physical and Chemical Hazards - Personal Protection X
HMIS	Health Hazards 3 *	Flammability 3	Physical Hazard 0	

Chronic Hazard Star Legend * = Chronic Health Hazard



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet