

### SECTION 1: Identification

#### 1.1. Identification

Product form	: Substance
Trade name	: <b>METHYL ETHYL KETONE (MEK)</b>
CAS No	: 78-93-3
Product code	: RX590239
Formula	: C4H8O
Synonyms	: 2-butanone / 2-oxobutane / 3-butanone / acetone, methyl- / A13-07540 / butan-2-one / butanone / Caswell NO 569 / ethyl methyl ketone / Ethyl methyl ketone (methyl ethyl ketone) / EXXON methylethyl ketone / FEMA N°. 2170 / ketone, ethyl methyl- / meetco / MEK (= methyl ethyl ketone) / methyl 2-propanone / methyl acetone
BIG no	: 10074

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	: Solvent Chemical raw material
------------------------------	------------------------------------

#### 1.3. Details of the supplier of the safety data sheet

: Rexall Solution  
27 Keefer Rd  
St. Catharines, ON SGT 4S1 4  
Tel: (844) 500-2436

#### 1.4. Emergency telephone number

Emergency number	: In the event of an emergency involving dangerous goods: in Canada call CANUTEC at 613-996-6666 or *666 on a cellular phone. in the US call CHEMTREC at 800-424-9300 (Account Name for US is Polyglass Coatings)
------------------	---

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification


Flam. Liq. 2 H225 - Highly flammable liquid and vapor  
Eye Irrit. 2A H319 - Causes serious eye irritation  
STOT SE 3 H336 - May cause drowsiness or dizziness

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H225 - Highly flammable liquid and vapor  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US)

: P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical/ventilating/lighting equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray  
P264 - Wash thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

# METHYL ETHYL KETONE (MEK)

## Safety Data Sheet

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a poison center or a doctor if you feel unwell  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>) to extinguish  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container in accordance with all local, regional, national and international regulations

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substance

Name	Product identifier	%	GHS-US classification
methyl ethyl ketone (Main constituent)	(CAS No) 78-93-3	100	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

Full text of H-phrases: see section 16

### 3.2. Mixture

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.
First-aid measures after inhalation	: Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.
First-aid measures after skin contact	: Wash immediately with lots of water. Soap may be used. Do not apply (chemical) neutralizing agents. Take victim to a doctor if irritation persists.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.
First-aid measures after ingestion	: Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Immediately call a poison center or doctor/physician. Consult a doctor/medical service if you feel unwell. Ingestion of large quantities: immediately to hospital.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Irritation of the nasal mucous membranes. Nausea. Headache. EXPOSURE TO HIGH CONCENTRATIONS: Irritation of the respiratory tract. Central nervous system depression. Dizziness. Mental confusion. Narcosis. Disturbances of consciousness.
Symptoms/injuries after skin contact	: Red skin. ON CONTINUOUS EXPOSURE/CONTACT: Dry skin. Cracking of the skin.
Symptoms/injuries after eye contact	: Irritation of the eye tissue. Inflammation/damage of the eye tissue.
Symptoms/injuries after ingestion	: AFTER ABSORPTION OF HIGH QUANTITIES: Symptoms similar to those listed under inhalation. Risk of aspiration pneumonia.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Itching. Skin rash/inflammation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Alcohol-resistant foam. Dry chemical powder. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

# METHYL ETHYL KETONE (MEK)

## Safety Data Sheet

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : DIRECT FIRE HAZARD. Highly flammable. Gas/vapour flammable with air within explosion limits. INDIRECT FIRE HAZARD. May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. Reactions involving a fire hazard: see "Reactivity Hazard".
- Explosion hazard : DIRECT EXPLOSION HAZARD. Gas/vapour explosive with air within explosion limits. INDIRECT EXPLOSION HAZARD. may be ignited by sparks. Reactions with explosion hazards: see "Reactivity Hazard".
- Reactivity : On heating: peroxidation resulting in increased fire or explosion risk. Upon combustion: CO and CO<sub>2</sub> are formed. Reacts violently with (strong) oxidizers: (increased) risk of fire/explosion. Violent to explosive reaction with many compounds e.g.: with (some) halogens compounds, alcohols and with (some) acids/bases. Prolonged storage: peroxidation resulting in increased fire or explosion risk.

### 5.3. Advice for firefighters

- Firefighting instructions : Cool tanks/drums with water spray/remove them into safety. Do not move the load if exposed to heat.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Protective goggles. Protective clothing. See "Material-Handling" to select protective clothing.
- Emergency procedures : Keep upwind. Mark the danger area. Consider evacuation. Seal off low-lying areas. Close doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Keep containers closed. Wash contaminated clothes.

#### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment.

### 6.2. Environmental precautions

- Prevent spreading in sewers.

### 6.3. Methods and material for containment and cleaning up

- For containment : Contain released substance, pump into suitable containers. Consult "Material-handling" to select material of containers. Plug the leak, cut off the supply. Dam up the liquid spill. Try to reduce evaporation. Measure the concentration of the explosive gas-air mixture. Dilute/disperse combustible gas/vapour with water curtain. Provide equipment/receptacles with earthing. Do not use compressed air for pumping over spills.
- Methods for cleaning up : Take up liquid spill into absorbent material, e.g.: sand, earth, vermiculite. Scoop absorbed substance into closing containers. See "Material-handling" for suitable container materials. Carefully collect the spill/leftovers. Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

- No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Handle uncleaned empty containers as full ones. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Do not use compressed air for pumping over. Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Observe normal hygiene standards. Avoid prolonged and repeated contact with skin. Keep container tightly closed. Before use: check for peroxides and eliminate them. Measure the concentration in the air regularly. Work under local exhaust/ventilation.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Remove contaminated clothes. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Keep container tightly closed.
- Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources. ignition sources.

# METHYL ETHYL KETONE (MEK)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Prohibitions on mixed storage	: KEEP SUBSTANCE AWAY FROM: oxidizing agents. (strong) acids. (strong) bases. halogens. alcohols. amines.
Storage area	: Store in a cool area. Keep out of direct sunlight. Store in a dark area. Ventilation at floor level. Fireproof storeroom. Provide for an automatic sprinkler system. Provide for a tub to collect spills. Provide the tank with earthing. May be stored under inert gas. Meet the legal requirements.
Special rules on packaging	: SPECIAL REQUIREMENTS: closing. dry. clean. opaque. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.
Packaging materials	: SUITABLE MATERIAL: stainless steel. monel steel. carbon steel. MATERIAL TO AVOID: synthetic material. aluminium. copper.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

METHYL ETHYL KETONE (MEK) (78-93-3)		
ACGIH	ACGIH TWA (ppm)	200 ppm (Methyl ethyl ketone (MEK); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (ppm)	300 ppm (Methyl ethyl ketone (MEK); USA; Short time value; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	URT irr; CNS & PNS impair
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	200 ppm

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Materials for protective clothing	: GIVE EXCELLENT RESISTANCE: No data available. GIVE GOOD RESISTANCE: butyl rubber. GIVE LESS RESISTANCE: No data available. GIVE POOR RESISTANCE: natural rubber. neoprene. nitrile rubber. polyethylene. PVC. viton.
Hand protection	: Gloves.
Eye protection	: Safety glasses.
Skin and body protection	: Head/neck protection. Protective clothing.
Respiratory protection	: Insufficient ventilation: wear respiratory protection.
Other information	: Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Colourless
Odor	: Sweet odour Acetone odour
Odor threshold	: 2 - 85 ppm 6 - 251 mg/m <sup>3</sup>
pH	: No data available
Melting point	: -86 °C (1013 hPa)
Freezing point	: No data available
Boiling point	: 80 °C (1013 hPa) -176 °F
Critical temperature	: 263 °C
Critical pressure	: 41550 hPa
Flash point	: -9 °C 15.8 °F
Relative evaporation rate (butyl acetate=1)	: 6
Relative evaporation rate (ether=1)	: 2.7
Flammability (solid, gas)	: No data available
Explosion limits	: 1.5 - 12 vol % 45 - 378 g/m <sup>3</sup>

# METHYL ETHYL KETONE (MEK)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: 105 hPa (20 °C)
Vapor pressure at 50 °C	: 370 hPa (50 °C)
Relative density	: 0.810 (20 °C)
Relative vapor density at 20 °C	: 2.4
Relative density of saturated gas/air mixture	: 1.2
Specific gravity / density	: 810 kg/m <sup>3</sup> (20 °C)
Molecular mass	: 72.11 g/mol
Solubility	: Soluble in water. Soluble in ethanol. Soluble in ether. Soluble in acetone. Soluble in oil. Water: 28 g/100ml Ethanol: Complete Ether: Complete Acetone: Complete
Log Pow	: 0.3 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 40 °C)
Auto-ignition temperature	: 404 °C 759 °F
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 0.00041 Pa.s (25 °C)
VOC	870 g/L - 7.25 lbs/USG

### 9.2. Other information

Minimum ignition energy	: 0.53 mJ
Specific conductivity	: 36000 pS/m
Saturation concentration	: 311 g/m <sup>3</sup>
VOC content (Regulatory - Less water and exempt solvents)	: 100 %
Other properties	: Gas/vapour heavier than air at 20°C. Clear. Volatile.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

On heating: peroxidation resulting in increased fire or explosion risk. Upon combustion: CO and CO<sub>2</sub> are formed. Reacts violently with (strong) oxidizers: (increased) risk of fire/explosion. Violent to explosive reaction with many compounds e.g.: with (some) halogens compounds, alcohols and with (some) acids/bases. Prolonged storage: peroxidation resulting in increased fire or explosion risk.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

Heat. No flames, No sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

amines. acids. strong acids. Strong bases. Oxidizing agent. Ammonia. copper. Copper alloys. Halogenated compounds. nitric acid. Hydrogen peroxide. Isocyanates. Strong mineral acids.

### 10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Likely routes of exposure	: Inhalation; Ingestion; Skin and eyes contact
Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.

# METHYL ETHYL KETONE (MEK)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Irritation of the nasal mucous membranes. Nausea. Headache. EXPOSURE TO HIGH CONCENTRATIONS: Irritation of the respiratory tract. Central nervous system depression. Dizziness. Mental confusion. Narcosis. Disturbances of consciousness.
Symptoms/injuries after skin contact	: Red skin. ON CONTINUOUS EXPOSURE/CONTACT: Dry skin. Cracking of the skin.
Symptoms/injuries after eye contact	: Irritation of the eye tissue. Inflammation/damage of the eye tissue.
Symptoms/injuries after ingestion	: AFTER ABSORPTION OF HIGH QUANTITIES: Symptoms similar to those listed under inhalation. Risk of aspiration pneumonia.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Itching. Skin rash/inflammation.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general	: Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008. Not classified as dangerous for the environment according to the criteria of Directive 67/548/EEC.
Ecology - air	: Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009). Not included in the list of fluorinated greenhouse gases (Regulation (EC) No 842/2006). TA-Luft Klasse 5.2.5.
Ecology - water	: Ground water pollutant. Not harmful to fishes (LC50(96h) >1000 mg/l). Slightly harmful to invertebrates (Daphnia) (EC50 (48h): 100 - 1000 mg/l). Not harmful to algae (EC50 (72h) >1000 mg/l). Not harmful to bacteria (EC50 >1000 mg/l). Not harmful to activated sludge.

#### METHYL ETHYL KETONE (MEK) (78-93-3)

EC50 Daphnia 1	308 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	2993 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Static system; Fresh water; Experimental value)

#### 12.2. Persistence and degradability

##### METHYL ETHYL KETONE (MEK) (78-93-3)

Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions.
Biochemical oxygen demand (BOD)	2.03 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.31 g O <sub>2</sub> /g substance
ThOD	2.44 g O <sub>2</sub> /g substance
BOD (% of ThOD)	> 0.5 (5 days; Literature study)

#### 12.3. Bioaccumulative potential

##### METHYL ETHYL KETONE (MEK) (78-93-3)

Log Pow	0.3 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 40 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

#### 12.4. Mobility in soil

##### METHYL ETHYL KETONE (MEK) (78-93-3)

Surface tension	0.024 N/m (20 °C)
Log Koc	Koc,34; Calculated value
Ecology - soil	Slightly harmful to plants.

#### 12.5. Other adverse effects

No additional information available

# METHYL ETHYL KETONE (MEK)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Waste disposal recommendations : Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Recycle by distillation. Remove to an authorized waste incinerator for solvents with energy recovery. Do not discharge into surface water. May be discharged to wastewater treatment installation.
- Additional information : Do not reuse empty containers.  
. Handle empty containers with care because residual vapors are flammable.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

- Transport document description : UN1193 Methyl ethyl ketone, 3, II
- UN-No.(DOT) : UN1193
- Proper Shipping Name (DOT) : Methyl ethyl ketone
- Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : II - Medium Danger
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
- DOT Packaging Bulk (49 CFR 173.xxx) : 242
- DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
- DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded
- Other information : No supplementary information available.

#### TDG

- Transport document description : UN1193 METHYL ETHYL KETONE (METHYL ETHYL KETONE), 3, II
- UN-No. (TDG) : UN1193
- TDG Proper Shipping Name : METHYL ETHYL KETONE
- TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids
- Packing group : II - Medium Danger
- Explosive Limit and Limited Quantity Index : 1
- Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 5

# METHYL ETHYL KETONE (MEK)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Transport by sea

UN-No. (IMDG)	: 1193
Proper Shipping Name (IMDG)	: ETHYL METHYL KETONE (METHYL ETHYL KETONE)
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger
EmS-No. (1)	: F-E
EmS-No. (2)	: S-D

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### METHYL ETHYL KETONE (MEK) (78-93-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Not listed on SARA Section 313 (Specific toxic chemical listings)

CERCLA RQ	5000 lb
-----------	---------

### 15.2. International regulations

#### CANADA

No additional information available

#### EU-Regulations

No additional information available

#### National regulations

No additional information available

### 15.3. US State regulations

#### METHYL ETHYL KETONE (MEK) (78-93-3)

State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
----------------------------	---

## SECTION 16: Other information

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness