

## EX014PR0700 - MTN PRO Glass to mirror converter



### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product identifier:** EX014PR0700 - MTN PRO Glass to mirror converter

**Other means of identification:**

**UFI:** 3YD1-10Q2-600T-HEDF

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Relevant uses: Spray paint

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:**

MONTANA COLORS, S.L.  
Pol. Ind. Pla de les Vives C/ Anaïs Nin 6  
08295 Sant Vicenç de Castellet - Barcelona - España  
Phone: +34 938332760 (9:00- 16:00h GMT +1:00)  
msds@montanacolors.com  
<https://www.montanacolors.com>

**1.4 Emergency telephone number:** +34 938332760 (Mon- frid 9:00- 16:00h GMT +1:00)

### SECTION 2: HAZARDS IDENTIFICATION \*\*

**2.1 Classification of the substance or mixture:**

**CLP Regulation (EC) No 1272/2008:**

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aerosol 1: Pressurised container: May burst if heated., H229

Aerosol 1: Flammable aerosols, Category 1, H222

Eye Irrit. 2: Eye irritation, Category 2, H319

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

**2.2 Label elements:**

**CLP Regulation (EC) No 1272/2008:**

Danger



**Hazard statements:**

Aerosol 1: H229 - Pressurised container: May burst if heated.

Aerosol 1: H222 - Extremely flammable aerosol.

Eye Irrit. 2: H319 - Causes serious eye irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

**Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P103: Read label before use.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P260: Do not breathe spray.

P271: Use only outdoors or in a well-ventilated area.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F

P501: Dispose of contents/container according to the separated collection system used in your municipality.

**Supplementary information:**

EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains maleic anhydride. May produce an allergic reaction.

**Substances that contribute to the classification**

Butanone; 1-methoxy-2-propanol; 2-methoxy-1-methylethyl acetate; Ethyl acetate

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**EX014PR0700 - MTN PRO Glass to mirror converter**

**SECTION 2: HAZARDS IDENTIFICATION \*\* (continued)**

**UFI:** 3YD1-10Q2-600T-HEDF

**2.3 Other hazards:**

Product fails to meet PBT/vPvB criteria  
Endocrine-disrupting properties: The product fails to meet the criteria.

\*\* Changes with regards to the previous version

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\***

**3.1 Substance:**

Non-applicable

**3.2 Mixture:**

**Chemical description:** Aerosol

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 115-10-6 EC: 204-065-8 Index: 603-019-00-8 REACH: 01-2119472128-37-XXXX	<b>Dimethyl ether<sup>(1)</sup></b> ATP CLP00		<b>30 - &lt;50 %</b>
	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger	
CAS: 78-93-3 EC: 201-159-0 Index: 606-002-00-3 REACH: 01-2119457290-43-XXXX	<b>Butanone<sup>(2)</sup></b> ATP CLP00		<b>30 - &lt;50 %</b>
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 107-98-2 EC: 203-539-1 Index: 603-064-00-3 REACH: 01-2119457435-35-XXXX	<b>1-methoxy-2-propanol<sup>(2)</sup></b> ATP ATP01		<b>2,5 - &lt;5 %</b>
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	<b>2-methoxy-1-methylethyl acetate<sup>(2)</sup></b> Self-classified		<b>2,5 - &lt;5 %</b>
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	
CAS: 141-78-6 EC: 205-500-4 Index: 607-022-00-5 REACH: 01-2119475103-46-XXXX	<b>Ethyl acetate<sup>(2)</sup></b> ATP CLP00		<b>1 - &lt;2,5 %</b>
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	<b>Xylene<sup>(3)</sup></b> Self-classified		<b>&lt;0,05 %</b>
	Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX	<b>Ethylbenzene<sup>(3)</sup></b> ATP ATP06		<b>&lt;0,05 %</b>
	Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	
CAS: 108-31-6 EC: 203-571-6 Index: 607-096-00-9 REACH: 01-2119472428-31-XXXX	<b>maleic anhydride<sup>(2)</sup></b> ATP ATP13		<b>&lt;0,05 %</b>
	Regulation 1272/2008	Acute Tox. 4: H302; Eye Dam. 1: H318; Resp. Sens. 1: H334; Skin Corr. 1B: H314; Skin Sens. 1A: H317; STOT RE 1: H372; EUH071 - Danger	

<sup>(1)</sup> Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878

<sup>(2)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

<sup>(3)</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**Other information:**

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**EX014PR0700 - MTN PRO Glass to mirror converter**

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\* (continued)**

Identification	Specific concentration limit
maleic anhydride CAS: 108-31-6 EC: 203-571-6	% (w/w) >=0,001: Skin Sens. 1A - H317

\*\* Changes with regards to the previous version

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

**SECTION 5: FIREFIGHTING MEASURES**

**5.1 Extinguishing media:**

**Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

**Unsuitable extinguishing media:**

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

- CONTINUED ON NEXT PAGE -



## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

#### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

### 6.2 Environmental precautions:

Avoid spillage into the aquatic environment as it contains substances potentially dangerous for this. Contain the product absorbed in hermetically sealed containers. In the case of serious spillage into the aquatic environment notify the relevant authority.

### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

### 6.4 Reference to other sections:

See sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 120 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

- CONTINUED ON NEXT PAGE -



**EX014PR0700 - MTN PRO Glass to mirror converter**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification		Occupational exposure limits		
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	IOELV (8h)	1000 ppm	1920 mg/m <sup>3</sup>	
	IOELV (STEL)			
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	IOELV (8h)	50 ppm	275 mg/m <sup>3</sup>	
	IOELV (STEL)	100 ppm	550 mg/m <sup>3</sup>	
Butanone CAS: 78-93-3 EC: 201-159-0	IOELV (8h)	200 ppm	600 mg/m <sup>3</sup>	
	IOELV (STEL)	300 ppm	900 mg/m <sup>3</sup>	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	IOELV (8h)	100 ppm	442 mg/m <sup>3</sup>	
	IOELV (STEL)	200 ppm	884 mg/m <sup>3</sup>	
Xylene CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>	
	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>	
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	IOELV (8h)	100 ppm	375 mg/m <sup>3</sup>	
	IOELV (STEL)	150 ppm	568 mg/m <sup>3</sup>	
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	IOELV (8h)	200 ppm	734 mg/m <sup>3</sup>	
	IOELV (STEL)	400 ppm	1468 mg/m <sup>3</sup>	

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1894 mg/m <sup>3</sup>	Non-applicable
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1161 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	600 mg/m <sup>3</sup>	Non-applicable
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	183 mg/kg	Non-applicable
	Inhalation	553,5 mg/m <sup>3</sup>	553,5 mg/m <sup>3</sup>	369 mg/m <sup>3</sup>	Non-applicable
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
	Inhalation	Non-applicable	550 mg/m <sup>3</sup>	275 mg/m <sup>3</sup>	Non-applicable
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	63 mg/kg	Non-applicable
	Inhalation	1468 mg/m <sup>3</sup>	1468 mg/m <sup>3</sup>	734 mg/m <sup>3</sup>	734 mg/m <sup>3</sup>
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	Non-applicable	293 mg/m <sup>3</sup>	77 mg/m <sup>3</sup>	Non-applicable
maleic anhydride CAS: 108-31-6 EC: 203-571-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	0,2 mg/m <sup>3</sup>	0,2 mg/m <sup>3</sup>	0,081 mg/m <sup>3</sup>	0,081 mg/m <sup>3</sup>

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	471 mg/m <sup>3</sup>	Non-applicable
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	31 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	412 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	106 mg/m <sup>3</sup>	Non-applicable

- CONTINUED ON NEXT PAGE -



**EX014PR0700 - MTN PRO Glass to mirror converter**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	Oral	Non-applicable	Non-applicable	33 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	78 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	43,9 mg/m <sup>3</sup>	Non-applicable
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	33 mg/m <sup>3</sup>	33 mg/m <sup>3</sup>
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Oral	Non-applicable	Non-applicable	4,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	37 mg/kg	Non-applicable
	Inhalation	734 mg/m <sup>3</sup>	734 mg/m <sup>3</sup>	367 mg/m <sup>3</sup>	367 mg/m <sup>3</sup>
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	15 mg/m <sup>3</sup>	Non-applicable

**PNEC:**

Identification				
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	STP	160 mg/L	Fresh water	0,155 mg/L
	Soil	0,045 mg/kg	Marine water	0,016 mg/L
	Intermittent	1,549 mg/L	Sediment (Fresh water)	0,681 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,069 mg/kg
Butanone CAS: 78-93-3 EC: 201-159-0	STP	709 mg/L	Fresh water	55,8 mg/L
	Soil	22,5 mg/kg	Marine water	55,8 mg/L
	Intermittent	55,8 mg/L	Sediment (Fresh water)	284,74 mg/kg
	Oral	1 g/kg	Sediment (Marine water)	284,7 mg/kg
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	STP	100 mg/L	Fresh water	10 mg/L
	Soil	4,59 mg/kg	Marine water	1 mg/L
	Intermittent	100 mg/L	Sediment (Fresh water)	52,3 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	5,2 mg/kg
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	100 mg/L	Fresh water	0,635 mg/L
	Soil	0,29 mg/kg	Marine water	0,064 mg/L
	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	STP	650 mg/L	Fresh water	0,24 mg/L
	Soil	0,148 mg/kg	Marine water	0,024 mg/L
	Intermittent	1,65 mg/L	Sediment (Fresh water)	1,15 mg/kg
	Oral	0,2 g/kg	Sediment (Marine water)	0,115 mg/kg
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	STP	9,6 mg/L	Fresh water	0,1 mg/L
	Soil	2,68 mg/kg	Marine water	0,01 mg/L
	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg
maleic anhydride CAS: 108-31-6 EC: 203-571-6	STP	44,6 mg/L	Fresh water	0,038 mg/L
	Soil	0,037 mg/kg	Marine water	0,004 mg/L
	Intermittent	0,379 mg/L	Sediment (Fresh water)	0,296 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,03 mg/kg

**8.2 Exposure controls:**

- CONTINUED ON NEXT PAGE -





**EX014PR0700 - MTN PRO Glass to mirror converter**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**



**A.- Individual protection measures, such as personal protective equipment**

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles		EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

**C.- Specific protection for the hands**





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



**D.- Eye and face protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Body protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

**F.- Additional emergency measures**

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

- CONTINUED ON NEXT PAGE -



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

V.O.C. (Supply):	99,8 % weight
V.O.C. density at 20 °C:	735,53 kg/m <sup>3</sup> (735,53 g/L)
Average carbon number:	4,11
Average molecular weight:	76,43 g/mol

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:	Aerosol
Appearance:	Not available
Colour:	According to the markings on the package
Odour:	Not available
Odour threshold:	Non-applicable *

**Volatility:**

Boiling point at atmospheric pressure:	-25 °C (Propellant)
Vapour pressure at 20 °C:	Non-applicable *
Vapour pressure at 50 °C:	<300000 Pa (300 kPa)
Evaporation rate at 20 °C:	Non-applicable *

**Product description:**

Density at 20 °C:	737 kg/m <sup>3</sup>
Relative density at 20 °C:	>0,737
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Recipient pressure:	Non-applicable *

**Flammability:**

Flash Point:	Non-applicable
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	240 °C (Propellant)
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *

**Particle characteristics:**

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

**9.2 Other information:**

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -





**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

**Information with regard to physical hazard classes:**

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	27,01 kJ/g
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

**Other safety characteristics:**

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases. Can react violently

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION \*\***

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:**

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**EX014PR0700 - MTN PRO Glass to mirror converter**

**SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)**

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Ethylbenzene (2B); Xylene (3)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) - single exposure:
 

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
  - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:
 

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	308,5 mg/L (4 h)	Rat
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	Rat
	LC50 inhalation	30 mg/L (4 h)	Rat
Butanone CAS: 78-93-3 EC: 201-159-0	LD50 oral	4000 mg/kg	Rat
	LD50 dermal	6400 mg/kg	Rabbit
	LC50 inhalation	23,5 mg/L (4 h)	Rat
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	LD50 oral	4100 mg/kg	Rat
	LD50 dermal	20000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L	

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**EX014PR0700 - MTN PRO Glass to mirror converter**

**SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)**

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Xylene CAS: 1330-20-7 EC: 215-535-7	2100 mg/kg	1100 mg/kg	Rat
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	3500 mg/kg	15354 mg/kg	Rat
maleic anhydride CAS: 108-31-6 EC: 203-571-6	17,2 mg/L (4 h)	>2000 mg/kg	Rabbit
	>2000 mg/kg	>2000 mg/kg	Rat
	>5 mg/L		

**11.2 Information on other hazards:**

**Endocrine disrupting properties**

Endocrine-disrupting properties: The product fails to meet the criteria.

**Other information**

Non-applicable

\*\* Changes with regards to the previous version

**SECTION 12: ECOLOGICAL INFORMATION \*\***

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Toxicity:**

**Acute toxicity:**

Identification	Concentration		Species	Genus
	LC50	EC50		
Butanone CAS: 78-93-3 EC: 201-159-0	3220 mg/L (96 h)	5091 mg/L (48 h)	Pimephales promelas	Fish
		4300 mg/L (168 h)	Daphnia magna	Crustacean
			Scenedesmus quadricauda	Algae
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	20800 mg/L (96 h)	23300 mg/L (48 h)	Pimephales promelas	Fish
		1000 mg/L (168 h)	Daphnia magna	Crustacean
			Selenastrum capricornutum	Algae
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	161 mg/L (96 h)	481 mg/L (48 h)	Pimephales promelas	Fish
		Non-applicable	Daphnia sp.	Crustacean
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	230 mg/L (96 h)	717 mg/L (48 h)	Pimephales promelas	Fish
		3300 mg/L (48 h)	Daphnia magna	Crustacean
			Scenedesmus subspicatus	Algae
Xylene CAS: 1330-20-7 EC: 215-535-7	>10 - 100 mg/L (96 h)	>10 - 100 mg/L (48 h)		Fish
		>10 - 100 mg/L (72 h)		Crustacean
				Algae
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	42,3 mg/L (96 h)	75 mg/L (48 h)	Pimephales promelas	Fish
		63 mg/L (3 h)	Daphnia magna	Crustacean
			Chlorella vulgaris	Algae

**Chronic toxicity:**

Identification	Concentration		Species	Genus
	NOEC	NOEC		
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	47,5 mg/L	100 mg/L	Oryzias latipes	Fish
			Daphnia magna	Crustacean
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	9,65 mg/L	2,4 mg/L	Pimephales promelas	Fish
			Daphnia magna	Crustacean
Xylene CAS: 1330-20-7 EC: 215-535-7	1,3 mg/L	1,17 mg/L	Oncorhynchus mykiss	Fish
			Ceriodaphnia dubia	Crustacean

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)**

Identification	Concentration		Species	Genus
	NOEC	Non-applicable		
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean

**12.2 Persistence and degradability:**

**Substance-specific information:**

Identification	Degradability		Biodegradability	
Butanone CAS: 78-93-3 EC: 201-159-0	BOD5	2,03 g O2/g	Concentration	Non-applicable
	COD	2,31 g O2/g	Period	20 days
	BOD5/COD	0,88	% Biodegradable	89 %
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5	Non-applicable	Concentration	785 mg/L
	COD	Non-applicable	Period	8 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	BOD5	1,36 g O2/g	Concentration	100 mg/L
	COD	1,69 g O2/g	Period	14 days
	BOD5/COD	0,8	% Biodegradable	83 %
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %

**12.3 Bioaccumulative potential:**

**Substance-specific information:**

Identification	Bioaccumulation potential	
Butanone CAS: 78-93-3 EC: 201-159-0	BCF	3
	Pow Log	0.29
	Potential	Low
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	BCF	3
	Pow Log	-0.44
	Potential	Low
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BCF	1
	Pow Log	0.43
	Potential	Low
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	BCF	30
	Pow Log	0.73
	Potential	Moderate
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BCF	1
	Pow Log	3.15
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	1,136E-2 N/m (25 °C)	Moist soil	Non-applicable

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**EX014PR0700 - MTN PRO Glass to mirror converter**

**SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)**

Identification	Absorption/desorption		Volatility	
	Koc		Henry	
Butanone CAS: 78-93-3 EC: 201-159-0	Koc	30	Henry	5,77 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,396E-2 N/m (25 °C)	Moist soil	Yes
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Koc	59	Henry	13,58 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,324E-2 N/m (25 °C)	Moist soil	Yes
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Koc	520	Henry	798,44 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes
maleic anhydride CAS: 108-31-6 EC: 203-571-6	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	1,673E-2 N/m (250,21 °C)	Moist soil	Non-applicable

**12.5 Results of PBT and vPvB assessment:**

Product fails to meet PBT/vPvB criteria

**12.6 Endocrine disrupting properties:**

Endocrine-disrupting properties: The product fails to meet the criteria.

**12.7 Other adverse effects:**

Not described

\*\* Changes with regards to the previous version

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Dangerous

**Type of waste (Regulation (EU) No 1357/2014):**

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2021 and RID 2021:

- CONTINUED ON NEXT PAGE -

**EX014PR0700 - MTN PRO Glass to mirror converter**



**SECTION 14: TRANSPORT INFORMATION (continued)**



- 14.1 UN number or ID number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS
- 14.3 Transport hazard class(es):** 2  
Labels: 2.1
- 14.4 Packing group:** N/A
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**  
Special regulations: 190, 327, 344, 625  
Tunnel restriction code: D  
Physico-Chemical properties: see section 9  
Limited quantities: 1 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 40-20:



- 14.1 UN number or ID number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS
- 14.3 Transport hazard class(es):** 2  
Labels: 2.1
- 14.4 Packing group:** N/A
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**  
Special regulations: 63, 959, 190, 277, 327, 344  
EmS Codes: F-D, S-U  
Physico-Chemical properties: see section 9  
Limited quantities: 1 L  
Segregation group: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2022:



- 14.1 UN number or ID number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS
- 14.3 Transport hazard class(es):** 2  
Labels: 2.1
- 14.4 Packing group:** N/A
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**  
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable  
 Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable  
 Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable  
 Article 95, REGULATION (EU) No 528/2012: Non-applicable

- CONTINUED ON NEXT PAGE -



**SECTION 15: REGULATORY INFORMATION (continued)**

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a	FLAMMABLE AEROSOLS	150	500

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

—tricks and jokes,

—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains Octamethylcyclotetrasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION**

**Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

COMMISSION REGULATION (EU) 2020/878

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- New declared substances  
1-methoxy-2-propanol (107-98-2)
- Removed substances  
2-butoxyethanol (111-76-2)

Substances that contribute to the classification (SECTION 2):

- New declared substances  
1-methoxy-2-propanol (107-98-2)

**Texts of the legislative phrases mentioned in section 2:**

H336: May cause drowsiness or dizziness.

H229: Pressurised container: May burst if heated.

H222: Extremely flammable aerosol.

H319: Causes serious eye irritation.

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) No 1272/2008:**

- CONTINUED ON NEXT PAGE -



## EX014PR0700 - MTN PRO Glass to mirror converter

### SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 4: H302 - Harmful if swallowed.  
Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.  
Acute Tox. 4: H332 - Harmful if inhaled.  
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
Eye Dam. 1: H318 - Causes serious eye damage.  
Eye Irrit. 2: H319 - Causes serious eye irritation.  
Flam. Gas 1A: H220 - Extremely flammable gas.  
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.  
Flam. Liq. 3: H226 - Flammable liquid and vapour.  
Press. Gas: H280 - Contains gas under pressure, may explode if heated.  
Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.  
Skin Irrit. 2: H315 - Causes skin irritation.  
Skin Sens. 1A: H317 - May cause an allergic skin reaction.  
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure (Inhalation).  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.  
STOT SE 3: H335 - May cause respiratory irritation.  
STOT SE 3: H336 - May cause drowsiness or dizziness.

#### Classification procedure:

STOT SE 3: Calculation method  
Aerosol 1: Calculation method  
Aerosol 1: Calculation method  
Eye Irrit. 2: Calculation method

#### Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

#### Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective concentration 50  
LogPOW: Octanolwater partition coefficient  
Koc: Partition coefficient of organic carbon  
UFI: unique formula identifier  
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -