

## Product information | TECHNICAL DATA SHEET

### RADIATOR PAINT

400 ml, 10.21 Oz, 318 g.

#### GENERAL DESCRIPTION

Satin solvent-based alkyd enamel for painting heating radiators, with good resistance to temperature and yellowing.

#### CHARACTERISTICS

- Good resistance to yellowing.
- Good covering power.
- Good hardening.
- Easy application and repainting.
- Durable shine.
- High resistance to scratches once the film has polymerized.
- Resistant to temperatures of up to 100°C.

#### APPLICATION

Due to the characteristics of the product, we recommend it for painting heating radiators.

- Decoration
- Industrial maintenance

#### INSTRUCTIONS FOR USE

- Before use, shake the can very well for about a minute after hearing the noise of the mixing ball
- Apply to clean and dry surfaces. Remove any corrosion with a wire brush. On painted surfaces remove the old non-adhered paint and sand the surface.
- Suitable for steel radiators. On non-ferrous materials, we recommend the application of a specific primer for the material to be painted.
- Apply the product in thin layers to obtain better results, painting two thin layers than one thick one. It can be repainted after ten minutes with the same paint.
- Do not apply to equipment connected to the mains and use in well ventilated areas.
- Safety data sheets are available.

#### GENERAL DESCRIPTION

Binder Type:	Alkyd
Colour:	White, Beige, Gray
Brightness (60°):	20-40% Satin
Dry to touch (ASTM D-1640 ISO 1517):	30'
Totally dry (ASTM D-1640 ISO 1517):	24-48 h
Dry layer thickness:	15 µ/layer
Adhesion (ASTM D-3359 ISO 2409):	B
Theoretical performance (continuous painting):	2.5 m <sup>2</sup> for 400ml aerosol
Thinner:	Esters
Recoating:	After 30' and before 2 h
Product life:	10 years (stored correctly)
Heat resistance of paint:	100°C
Application conditions:	Ambient temperature 8°C
	Surface temperature 5-35°C
	Humidity Max. 85% R.H.P

Adhesion tests have been carried out on steel plates.

280421

#### IMAGE



#### LABEL



#### CAP SYSTEM



**Pocket Cap**  
Fino - Fine

Blanco / White  
EX014PRO020

Gris / Grey  
EX014PRO021

Beige / Beige  
EX014PRO022

#### PACKAGING

Capacity 400 ml.  
Packaging heat resistance: <50°C  
Propellant: Beige, gray: GLP C3-C4, White: DME

**Box (6 units)**  
205 X 140 X 200 mm

