



# Product information | TECHNICAL DATA SHEET

#### **ANTI RUST PRIMER**

400 ml, 10.7 Oz, 304 g.

#### **GENERAL DESCRIPTION**

Anti rust primer formulated with acrylic resins and corrosion inhibitor pigments, makes it ideal for protecting any iron surface.

#### **FEATURES**

- Fast drying.
- Good elasticity.
- Easy of application and recoating.
- Good adherence.
- Does not contain lead.
- High covering power.
- Very high resistance to outdoor exposure.
- High anti-corrosion power.

#### **APPLICATIONS**

Suitable as primer in spray paint systems. Its anticorrosive power makes it ideal as a primer coat for protecting any iron surface.

- Automotive industry

- Industrial aplications
- Metal structures

- DYI
- Maintenance

## INSTRUCTIONS FOR USE

- Shake can vigorously for one minute after hearing mixer noise.
- Thoroughly clean, degrease, and dry the object to be painted. On rusty metallic surfaces, remove corrosion using a wire brush.
- Apply thin coats for best results, always thin layers is better than one thick, paintable after ten minutes with the same paint.
- Disconnect the electrical appliance before painting. Use it in well ventilated areas.
- Request safety data sheets.

### PHYSICAL PROPERTIES

Brinder type:	Acrylic
Color:	Gray, Rec
Dry to the touch (ASTM D-1640 ISO 1517):	10
Total drying (ASTM D-1640 ISO 1517):	30
Thickness of dry layer (ASTM D-823 ISO 2808):	15 μ/layer
Adherence (ASTM D-3359 ISO 2409):	Е
Theoretical coverage (continuous painting):	2,5 m <sup>2</sup> for 400 m
	0,70 m <sup>2</sup> for 150 m
Thinner:	Butyl Acetate
Product life:	(Well Stored) 5 Years
Recoating:	After 10
Painted resistance to heat:	160°C
Application conditions:	Ambient temperature 8°C
	Surface temperature 5-50°C
	Humidity Max. 85% R.H.F
*Adherence tests were performed on steel.	280421

#### **IMAGE**



LID Protects the valve and the nozzle.

LABEL **CAP SYSTEM** 





Fino - Fine

Gris / Grey EX014PR0115

Rojo / Red

#### **PACKAGING**

Nominal capacity 400 ml. Heat resistanve of packaging: <50°C Propellant: DME

Box (6 units)

205 X 140 X 200 mm.









